

CM ICH

Climatic Chamber for Stability Test

- Economical
- Ideal for pharmaceutical industry
- 1 or 2 doors.
- Easy to use, and reliable.
- Optional independent cabinets



The DYCOMETAL stability chamber have been designed to store pharmaceutical products, biotechnological, dermoaesthetic, veterinarians, hospital, etc.., according to ICH and FDA standards.

From more than 25 years, our company has specialized in providing technological support to companies in the pharmaceutical sector.

These type of chambers are available in en 2 volumes: 500 and 1000 liters.

DYCOMETAL EQUIPOS DE C.C., S.L.

C/ De la Ciència, 35-37 08840 - Viladecans (Barcelona) - SPAIN T: (34) 936 526 610 F: (34) 936 407 60

CONTROL:

The intelligence of the system is based on using 1 controller / logger for measuring and independent regulation of temperature and humidity, located on the front panel of the control situation with ergonomic switches and indicator lights.

- Parameter monitoring temperature or humidity reading to visualize real value and setpoint.
- Retention of work values entered in case of power failure.





- Optimization of work values by PID parameters in cold and heat.
- Configuring alarms warn when exceeding a safety limit value or for some reason there is a diversion of the conditions of control.
- Direct reading moisture%. H. R.
- $^{\circ}$ Direct reading of temperature in $^{\circ}$ C

FEATURES:

Model			CM-0/500 ICH	CM-0/1000 ICH
Volume		liters	473	1042
Workspace	Height	mm	1487	1487
	Width	mm	582	1282
	Depth	mm	547	547
External dimensions	Height	mm	2075	2075
	Width	mm	700	1400
	Depth	mm	819	819
lemperature range		°C	+20 to +70°C	
Temperature stability		°C	±0,1 °C to ±0,3°C	
Temperature uniformity		% C	±0,5 °C to ±1,5°C	
Humidity range		% RH	50 to 90% RH	
lumidity stability %		% RH	±1%RH to ±3%RH	
Shelves			4	8
Weight		Kg	150	210
Power		V	220V 50Hz.	

C/ De la Ciència, 3*5-37*

08840 - Viladecans (Barcelona) - SPAIN

r. (34) 936 526 610 F. (34) 936 407 607

www.dycometal.com